



## EVERYDAY PRINT WINDOW OPAQUE

2-Way Window Graphics

### Product Codes SPPWCIIIIGL

Everyday Print Window Opaque is an opaque printable block out film ideal for two-sided window graphics and other block out layer needs. To create eye-catching two-sided window graphics, simply combine with a reverse printed clear print media such as Everyday Print Window Clear.

Everyday Print Window Opaque's high opacity prevents graphics from showing through on the other side when using as a cover up graphic or label.

- **CREATE DOUBLE-SIDED WINDOW GRAPHICS WITHOUT THE NEED FOR INK LAYERS OR WHITE INK.**
- **IDEAL FOR PREVENTING GRAPHIC SHOWTHROUGH ON OTHER SIDE**



FINISHES: Matte

**5.9**  
mil

Opaque  
White  
Polymeric



(Eco) Solvent, Latex, UV



Permanent Acrylic  
Pressure-Sensitive  
Adhesive



54" x 150'



7 Years Durability  
(w. matching laminate)

# HASCO GRAPHICS

Equipment, Service & Supplies since 1966



## APPLICATIONS

**2-SIDED WINDOW GRAPHICS**

**SMOOTH GLASS SURFACES**

**POINT OF SALE GRAPHICS**

**DECALS & STICKERS**



ENGINEERED BY

**DRYTAC**  
ADHESIVE SCIENCE



Everyday Print Window Opaque is an opaque printable block out film ideal for two-sided window graphics and other block out layer needs. To create eye-catching two-sided window graphics, simply combine with a reverse printed clear print media such as Everyday Print Window Clear.

Everyday Print Window Opaque's high opacity prevents graphics from showing through on the other side when using as a cover up graphic or label.

Please contact us for more information, performance and warranty guidelines.



© 2023 Hasco Graphics

## WINDOW OPAQUE TECHNICAL SPECIFICATIONS

### PRODUCT STRUCTURE

<b>Film</b>	Opaque Matte White Film
<b>Adhesive</b>	Permanent Acrylic Pressure-Sensitive
<b>Release Liner</b>	78# Clay Coated

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	5.9 mil (149.86μ)
<b>Adhesive Layer</b>	1.2 mil (30.48μ)
<b>Outdoor Durability</b>	7 Years (ink dependent and with matching overlaminate)
<b>Application Temperature</b>	-4°F (-20°C)
<b>Service Temperature Range</b>	-49°F to 230°F (-45°C to 110°C)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

ENGINEERED BY  
**DRYTAC**  
ADHESIVE SCIENCE