



Date	Module	Power Supply	Modules per Foot	Area
July 10, 2024 11:34 AM PDT	(6) PosterBox Slim 2 6500K	(1) Energizer Series Universal 60W	2.400	6.00 sq ft
Layout Type	Module Part Number	Power Supply Part Number	Row Spacing	Perimeter
Side Lit	701946-6WXP3	P-OH060-12-EC	N/A	10.00 feet
Total Watts	Module SKU	Power Supply SKU	Can Depth	Max Modules per PS
10.08 watts		P-OH060-12-EC	4.00 in	30

NOTICE: THIS LAYOUT IS ONLY AN ESTIMATE

Channel letter depth, face color, materials, and thickness can vary, which may affect the number of modules required. To ensure accuracy, it is recommended that you test light in a darkened environment prior to installing or shipping to the site to ensure that the light output is commercially acceptable. Final material estimates are the responsibility of the sign manufacturer.

ALL LAYOUTS ARE BASED ON THE USE OF ACRYLIC FACES.

THESE DRAWINGS AND SPECIFICATIONS ARE THE CONFIDENTIAL PROPERTY OF PRINCIPAL SLOAN. ANY REPRODUCTION OR USE WITHOUT PRIOR WRITTEN CONSENT IS PROHIBITED.

Channel Letter Lighting?


WE'VE GOT THAT!

- Available in Micro, Mini, Spec, HO & Deep
- All sizes available in 3000 K, 4100 K, 5000 K, 6500 K, 7100 K
- Mini & Spec available in Red, Green & Blue

Prism
synergy

PRINCIPAL SLOAN
We Speak Sign Language

24 VDC



3490 Venture Dr.
San Angelo, TX 76905
325.227.4577
www.principalsloan.com
layouts@pindustries.com

Cabinet Details

Width	24.0 in	Module Spacing	6.0 in
Height	36.0 in	Module Count	6
Can Depth	4.00 in	Module Color	White (6500K)
Orientation	Vertical	Module Watts	10.08 watts
Sides	Double	Module Voltage	12v
Area	6.00 sq ft	Watts per Module	1.68 watts
Perimeter	10.00 feet	Total Lumens	1110
Row Spacing	N/A	Average Lumens per Watt	110
Power Supply Location	Self-contained	Total Module Length	2.50 ft
Power Supply Count	1	Horizontal Clearance	0.5 in
Power Supply Mode	Optimal by Run	Vertical Clearance	3.0 in
Amp Draw	1.350	Ordering Length	4.3 feet
Job ID		Center Pole Diameter	6.0 in

Modules Used

Module Name	Module Part Number	Count
PosterBox Slim 2 6500K	701946-6WXL3	6

Power Supplies

PS #	Name	Part Number	Max Watts	Load	Module Count	Row #s	Module Watts	Modules
1	Energizer Series Universal 60W	P-OH060-12-EC	10.08	16.8 %	6.0	1	10.08	

NOTICE: THIS LAYOUT IS ONLY AN ESTIMATE

Channel letter depth, face color, materials, and thickness can vary, which may affect the number of modules required. To ensure accuracy, it is recommended that you test light in a darkened environment prior to installing or shipping to the site to ensure that the light output is commercially acceptable. Final material estimates are the responsibility of the sign manufacturer.

ALL LAYOUTS ARE BASED ON THE USE OF ACRYLIC FACES.

THESE DRAWINGS AND SPECIFICATIONS ARE THE CONFIDENTIAL PROPERTY OF PRINCIPAL SLOAN. ANY REPRODUCTION OR USE WITHOUT PRIOR WRITTEN CONSENT IS PROHIBITED.

Channel Letter Lighting?

WE'VE GOT THAT!

- Available in Micro, Mini, Spec, HO & Deep
- All sizes available in 3000 K, 4100 K, 5000 K, 6500 K, 7100 K
- Mini & Spec available in Red, Green & Blue

Prism energy

PRINCIPAL SLOAN We Speak Sign Language

LIFE SPAN 24 VDC